R9 290X LIGHTNING

MSí [°]Graphics Card





Product Specification		Technology Support	
Product Name	R9 290X LIGHTNING	Afterburner OC	GPU/Memory/VDDCI
GPU	AMD Radeon R9 290X	DirectX	11.2
Codename	Hawaii XT	OpenGL	4.3
Processors	2816 Units	Multi-GPU	CrossFire, 4-way(SW)
Core Clock	1080 MHz	Multi-Display	Eyefinity
Memory Clock	5000 MHz	3D Technology	HD3D
· · ·		Power Saving	PowerTune
Memory Size	4GB GDDR5	HDCP Capable	γ
Memory Bus	512 bits	Accessory	
Outputs	DisplayPort / HDMI DL-DVI-D*2	Driver CD	Y
Power Consumption	250W	Installation Guide	Y
Card Dimension	302x131x55 mm	DVI to VGA Dongle	N
Card Weight	1580g	Power Cable	6pin*1, 8pin*2
		V-check Point	Y, 3
Form Factor	ATX	MOS Sink	Y, 1

Triple Force Architecture

- Triple Level Signals Show the real-time GPU load by different colors.
- TriFrozr Thermal Design –Triple PWM
 fans with Independent Control System on
- Pure Digital PWM Control Digitally controlled GPU, Memory and VDDCI



Twin BIOS & Enhanced Power

- **Twin BIOS** Separated BIOS chips for regular use and LN2 overclocking
- Enhanced Power 12 GPU phases and 3 Memory phases on a custom designed 12 layers PCB for amazing overclocking potential.



Military Class 4 Components

- Components pass MIL-STD-810G certification for the best stability and quality
- Equipped with CopperMOS, Hi-C CAPs, New SFC and All Dark Solid CAPs.

3X3 OC Kits

- Triple Overvoltage: Total control with GPU, Memory and PLL voltage adjustment
- **Triple Temp Monitor**: Real time Monitoring of GPU, Memory and PLL conditions.
- V-Check point: For direct and accurate read-out of GPU, memory and PLL voltage

